


## Geberit PE Abzweig 88,5°



Beispielbild



### Verwendungszwecke

- Zur Gebäudeentwässerung

### Technische Daten

Werkstoff

PE-HD

Art.-Nr.	DN	d, Ø	d1, Ø	arc	H	X1	X2	X3	K1	K2	K3	V E1	VE2	VE3	VE4
379.158.16.1	30 / 30	32 mm	32 mm	88.5 °	8.5 cm	5 cm	3.5 cm	3.5 cm	2.5 cm	1 cm	1 cm	1 St.	10 St.		
360.158.16.1	40 / 30	40 mm	32 mm	88.5 °	13 cm	7.5 cm	5.5 cm	5.5 cm	5 cm	2.5 cm	2 cm	1 St.	10 St.		
360.159.16.1	40 / 40	40 mm	40 mm	88.5 °	13 cm	7.5 cm	5.5 cm	5.5 cm	4.5 cm	2.5 cm	2.5 cm	1 St.	10 St.	50 St.	
362.160.16.1	40	48 mm	48 mm	88.5 °	23.5 cm	20 cm	3.5 cm	3.5 cm	16 cm	0 cm	0 cm	1 St.	10 St.	40 St.	640 St.
361.159.16.1	50 / 40	50 mm	40 mm	88.5 °	15 cm	9 cm	6 cm	6 cm	6 cm	2.5 cm	3 cm	1 St.	10 St.		
361.162.16.1	50 / 50	50 mm	50 mm	88.5 °	15 cm	9 cm	6 cm	6 cm	5.5 cm	2.5 cm	2.5 cm	1 St.	10 St.	50 St.	800 St.
363.162.16.1	56 / 50	56 mm	50 mm	88.5 °	17.5 cm	10.5 cm	7 cm	7 cm	7 cm	3 cm	3.5 cm	1 St.	10 St.		
363.165.16.1	56 / 56	56 mm	56 mm	88.5 °	17.5 cm	10.5 cm	7 cm	7 cm	6.5 cm	3 cm	3 cm	1 St.	10 St.	30 St.	
364.159.16.1	60 / 40	63 mm	40 mm	88.5 °	17.5 cm	10.5 cm	7 cm	7 cm	7 cm	3 cm	3 cm	1 St.			
364.162.16.1	60 / 50	63 mm	50 mm	88.5 °	17.5 cm	10.5 cm	7 cm	7 cm	7 cm	3 cm	3.5 cm	1 St.	10 St.		
364.165.16.1	60 / 56	63 mm	56 mm	88.5 °	17.5 cm	10.5 cm	7 cm	7 cm	6.5 cm	3 cm	3 cm	1 St.	10 St.	120 St.	
364.170.16.1	60 / 60	63 mm	63 mm	88.5 °	17.5 cm	10.5 cm	7 cm	7 cm	6 cm	3 cm	3 cm	1 St.	10 St.	120 St.	
365.159.16.1	70 / 40	75 mm	40 mm	88.5 °	17.5 cm	10.5 cm	7 cm	7 cm	7.5 cm	2.5 cm	4 cm	1 St.	10 St.		
365.162.16.1	70 / 50	75 mm	50 mm	88.5 °	17.5 cm	10.5 cm	7 cm	7 cm	7 cm	2.5 cm	3.5 cm	1 St.	10 St.	90 St.	360 St.
365.165.16.1	70 / 56	75 mm	56 mm	88.5 °	17.5 cm	10.5 cm	7 cm	7 cm	6.5 cm	2.5 cm	3 cm	1 St.	10 St.	90 St.	
365.170.16.1	70 / 60	75 mm	63 mm	88.5 °	17.5 cm	10.5 cm	7 cm	7 cm	6 cm	2.5 cm	2.5 cm	1 St.	10 St.	100 St.	
365.175.16.1	70 / 70	75 mm	75 mm	88.5 °	17.5 cm	10.5 cm	7 cm	7 cm	5.5 cm	2.5 cm	2.5 cm	1 St.	10 St.	80 St.	
366.159.16.1	90 / 40	90 mm	40 mm	88.5 °	20 cm	12 cm	8 cm	8 cm	8.5 cm	2.5 cm	4.5 cm	1 St.	60 St.		
366.162.16.1	90 / 50	90 mm	50 mm	88.5 °	20 cm	12 cm	8 cm	8 cm	8.5 cm	2.5 cm	4.5 cm	1 St.	10 St.		

Art.-Nr.	DN	d, ø	d1, ø	arc	H	X1	X2	X3	K1	K2	K3	V E1	VE2	VE3	VE4
366.165.16.1	90 / 56	90 mm	56 mm	88.5 °	20 cm	12 cm	8 cm	8 cm	8 cm	2.5 cm	4 cm	1 St.	10 St.		
366.170.16.1	90 / 60	90 mm	63 mm	88.5 °	20 cm	12 cm	8 cm	8 cm	7.5 cm	2.5 cm	3.5 cm	1 St.	60 St.		
366.175.16.1	90 / 70	90 mm	75 mm	88.5 °	20 cm	12 cm	8 cm	8 cm	7 cm	2.5 cm	3 cm	1 St.	10 St.		
366.180.16.1	90 / 90	90 mm	90 mm	88.5 °	20 cm	12 cm	8 cm	8 cm	6.5 cm	2.5 cm	2.5 cm	1 St.	10 St.	160 St.	
367.159.16.1	100 / 40	110 mm	40 mm	88.5 °	22.5 cm	13.5 cm	9 cm	9 cm	10 cm	2.5 cm	6 cm	1 St.	40 St.		
367.162.16.1	100 / 50	110 mm	50 mm	88.5 °	22.5 cm	13.5 cm	9 cm	9 cm	9.5 cm	2.5 cm	5 cm	1 St.	10 St.	160 St.	480 St.
367.165.16.1	100 / 56	110 mm	56 mm	88.5 °	22.5 cm	13.5 cm	9 cm	9 cm	9 cm	2.5 cm	4.5 cm	1 St.	35 St.	140 St.	420 St.
367.170.16.1	100 / 60	110 mm	63 mm	88.5 °	22.5 cm	13.5 cm	9 cm	9 cm	9 cm	2.5 cm	4 cm	1 St.	40 St.		
367.175.16.1	100 / 70	110 mm	75 mm	88.5 °	22.5 cm	13.5 cm	9 cm	9 cm	8.5 cm	2.5 cm	3.5 cm	1 St.	35 St.	140 St.	
367.180.16.1	100 / 90	110 mm	90 mm	88.5 °	22.5 cm	13.5 cm	9 cm	9 cm	7.5 cm	2.5 cm	3 cm	1 St.	10 St.	30 St.	
367.185.16.1	100 / 100	110 mm	110 mm	88.5 °	22.5 cm	13.5 cm	9 cm	9 cm	6.5 cm	2 cm	2 cm	1 St.	30 St.	120 St.	480 St.
368.162.16.1	125 / 50	125 mm	50 mm	88.5 °	25 cm	15 cm	10 cm	10 cm	11 cm	2.5 cm	6 cm	1 St.	5 St.		
368.165.16.1	125 / 56	125 mm	56 mm	88.5 °	25 cm	15 cm	10 cm	10 cm	10.5 cm	2.5 cm	5.5 cm	1 St.	5 St.		
368.170.16.1	125 / 60	125 mm	63 mm	88.5 °	25 cm	15 cm	10 cm	10 cm	10.5 cm	2.5 cm	5 cm	1 St.	5 St.		
368.175.16.1	125 / 70	125 mm	75 mm	88.5 °	25 cm	15 cm	10 cm	10 cm	10 cm	2.5 cm	4.5 cm	1 St.	5 St.		
368.180.16.1	125 / 90	125 mm	90 mm	88.5 °	25 cm	15 cm	10 cm	10 cm	9 cm	2.5 cm	4 cm	1 St.	5 St.		
368.185.16.1	125 / 100	125 mm	110 mm	88.5 °	25 cm	15 cm	10 cm	10 cm	8 cm	2 cm	3 cm	1 St.	25 St.		
368.189.16.1	125 / 125	125 mm	125 mm	88.5 °	25 cm	15 cm	10 cm	10 cm	7 cm	2 cm	2 cm	1 St.	20 St.		
369.175.16.1	150 / 70	160 mm	75 mm	88.5 °	35 cm	21 cm	14 cm	14 cm	15 cm	4.5 cm	8 cm	1 St.			
369.185.16.1	150 / 100	160 mm	110 mm	88.5 °	35 cm	21 cm	14 cm	14 cm	13.5 cm	4.5 cm	6 cm	1 St.	5 St.		
369.189.16.1	150 / 125	160 mm	125 mm	88.5 °	35 cm	21 cm	14 cm	14 cm	12.5 cm	4.5 cm	5 cm	1 St.			
369.195.16.1	150 / 150	160 mm	160 mm	88.5 °	35 cm	21 cm	14 cm	14 cm	10.5 cm	3.5 cm	3 cm	1 St.	5 St.		
370.180.16.1	200 / 90	200 mm	90 mm	88.5 °	36 cm	18 cm	18 cm	18 cm	0 cm	3 cm	0 cm				
370.185.16.1	200 / 100	200 mm	110 mm	88.5 °	36 cm	18 cm	18 cm	18 cm	0 cm	3 cm	0 cm	1 St.			
370.189.16.1	200 / 125	200 mm	125 mm	88.5 °	36 cm	18 cm	18 cm	18 cm	0 cm	3 cm	0 cm	1 St.			
370.195.16.1	200 / 150	200 mm	160 mm	88.5 °	36 cm	18 cm	18 cm	18 cm	0 cm	2 cm	0 cm	1 St.			

Art.-Nr.	DN	d, ø	d1, ø	arc	H	X1	X2	X3	K1	K2	K3	V E1	VE2	VE3	VE4
370.196.16.1	200 / 200	200 mm	200 mm	88.5 °	40 cm	20 cm	20 cm	20 cm	0 cm	0 cm	0 cm	1 St.			
371.185.16.1	250 / 100	250 mm	110 mm	88.5 °	44 cm	22 cm	22 cm	22 cm	3.5 cm	4 cm	3.5 cm	1 St.			
371.189.16.1	250 / 125	250 mm	125 mm	88.5 °	44 cm	22 cm	22 cm	22 cm	3 cm	4 cm	3 cm	1 St.			
371.195.16.1	250 / 150	250 mm	160 mm	88.5 °	44 cm	22 cm	22 cm	22 cm	0 cm	3.5 cm	0 cm	1 St.			
371.196.16.1	250 / 200	250 mm	200 mm	88.5 °	48 cm	24 cm	24 cm	24 cm	0 cm	0 cm	0 cm	1 St.			
371.197.16.1	250 / 250	250 mm	250 mm	88.5 °	48 cm	24 cm	24 cm	24 cm	0 cm	0 cm	0 cm	1 St.			
372.185.16.1	300 / 100	315 mm	110 mm	88.5 °	56 cm	28 cm	28 cm	28 cm	9.5 cm	6 cm	9.5 cm	1 St.			
372.189.16.1	300 / 125	315 mm	125 mm	88.5 °	56 cm	28 cm	28 cm	28 cm	9 cm	6 cm	9 cm	1 St.			
372.195.16.1	300 / 150	315 mm	160 mm	88.5 °	56 cm	28 cm	28 cm	28 cm	7 cm	6 cm	7 cm	1 St.			
372.196.16.1	300 / 200	315 mm	200 mm	88.5 °	56 cm	28 cm	28 cm	28 cm	4.5 cm	0 cm	4.5 cm	1 St.			
372.197.16.1	300 / 250	315 mm	250 mm	88.5 °	56 cm	28 cm	28 cm	28 cm	2 cm	0 cm	2 cm	1 St.			
372.198.16.1	300 / 300	315 mm	315 mm	88.5 °	56 cm	28 cm	28 cm	28 cm	0 cm	0 cm	0 cm	1 St.			