


Geberit PE Hosenabzweig 2 x 30°



Beispielbild



Verwendungszwecke

- Zur Gebäudeentwässerung
- Zum vertikalen Einbau

Technische Daten

Werkstoff

PE-HD

Art-Nr.	DN	d, ø	d1, ø	arc	X1	X2	K1	K2	VE1	VE2
361.459.16.1	50 / 40	50 mm	40 mm	60 °	5.5 cm	11 cm	4 cm	5 cm	1 St.	10 St.
361.462.16.1	50 / 50	50 mm	50 mm	60 °	5.5 cm	11 cm	3 cm	4 cm	1 St.	
363.462.16.1	56 / 50	56 mm	50 mm	60 °	6 cm	12 cm	4 cm	5 cm	1 St.	10 St.
363.465.16.1	56 / 56	56 mm	56 mm	60 °	1.8 cm	5.3 cm	0 cm	0 cm	1 St.	10 St.
364.462.16.1	60 / 50	63 mm	50 mm	60 °	6.5 cm	13 cm	5 cm	6 cm	1 St.	
364.465.16.1	60 / 56	63 mm	56 mm	60 °	6.5 cm	13 cm	4 cm	6 cm	1 St.	
365.462.16.1	70 / 50	75 mm	50 mm	60 °	7 cm	14 cm	6 cm	7 cm	1 St.	10 St.
365.465.16.1	70 / 56	75 mm	56 mm	60 °	7 cm	14 cm	6 cm	7 cm	1 St.	10 St.
365.470.16.1	70 / 60	75 mm	63 mm	60 °	7 cm	14 cm	5 cm	6 cm	1 St.	
367.480.16.1	100 / 90	110 mm	90 mm	60 °	9 cm	18 cm	7 cm	7 cm		
367.481.16.1	100 / 100	110 mm	110 mm	60 °	9 cm	10.2 cm	5 cm	0 cm	1 St.	